



No measures are required.

Useable with measures.

Reduce exposure duration.

| Typ | daily exposure time [h] | time sequence operating mode (idling/full load/nom. speed) | standard | vibration total value handle left idling a hv [m/s ²] | vibration total value handle right idling a hv [m/s ²] | vibration total value handle left nom. speed a hv [m/s ²] | vibration total value handle right nom. speed a hv [m/s ²] | equivalent vibration level handle left a hv,eq [m/s ²] | equivalent vibration level handle right a hv,eq [m/s ²] | daily vibration exposure handle left A(8) [m/s ²] | daily vibration exposure handle right A(8) [m/s ²] |
|----------|-------------------------|--|----------|---|--|---|--|--|---|---|--|
| HL 45 | 2,0 | 1/5 / - / 4/5 | ISO 8662 | 7,2 | 3,5 | 6,4 | 7,6 | 6,6 | 7,0 | 3,3 | 3,5 |
| HL 75 K | 2,0 | 1/5 / - / 4/5 | ISO 7916 | 2,4 | 2,2 | 7,8 | 7,7 | 7,1 | 7,0 | 3,5 | 3,5 |
| HL 75 | 2,0 | 1/5 / - / 4/5 | ISO 7916 | 2,6 | 1,9 | 6,1 | 7,3 | 5,6 | 6,6 | 2,8 | 3,3 |
| HL 100 K | 2,0 | 1/5 / - / 4/5 | ISO 8662 | 2,3 | 1,8 | 4,3 | 5,1 | 4,0 | 4,6 | 2,0 | 2,3 |
| HL 100 | 2,0 | 1/5 / - / 4/5 | ISO 8662 | 2,7 | 1,5 | 4,5 | 5,4 | 4,2 | 4,9 | 2,1 | 2,5 |

All data is subject to change and applicable to European versions only.